



# F-Type Nuts

## MAX-FORCE SERIES F-8.4 & F-8.10

with RADIALLY LOCATED F-NIPPLE and RELEASE SCREW

Actuated by manual or motorized grease pump. Self-aligning annular thrust ring with 4 or 10 mm maximum axial travel.

Model	Max Arbor Thread Size		Cannot Exceed Minimum Tool Ø		Verify diameters D & E contact an uninterrupted surface				Select Stroke as Required		Ensure Adequate Force Has Been Selected						Weight	
	Max Thread Ø		Nut Diameter		Thrust Ring Size				Thrust Ring Stroke		Nut Width		Clamping Force					
	A		B		D - OD		E - ID		S		C		400 BAR		700 BAR		KG	Pounds
	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	kN	Tons	kN	Tons		
F-8.415.5	218	8.500	282	11.102	260	10.236	235	9.252	4	0.157	50	1.969	389	43	680	76	13.0	28.6
F-8.415.5	218	8.500	288	11.339	260	10.236	235	9.252	10	0.394	60	2.362	389	43	680	76	14.0	30.8
F-8.416.1	226	8.875	292	11.496	270	10.630	245	9.646	4	0.157	50	1.969	404	45	707	79	10.0	22.0
F-8.1016.1	226	8.875	298	11.732	270	10.630	245	9.646	10	0.394	60	2.362	404	45	707	79	11.5	25.3
F-8.417.0	242	9.500	305	12.008	285	11.220	260	10.236	4	0.157	50	1.969	428	48	749	84	12.0	26.4
F-8.1017.0	242	9.500	313	12.323	285	11.220	260	10.236	10	0.394	60	2.362	428	48	749	84	14.0	30.8
F-8.418.0	260	10.250	338	13.307	310	12.205	280	11.024	4	0.157	55	2.165	556	62	973	109	14.0	30.8
F-8.1018.0	260	10.250	344	13.543	310	12.205	280	11.024	10	0.394	65	2.559	556	62	973	109	16.5	36.3
F-8.419.0	280	11.000	358	14.094	330	12.992	300	11.811	4	0.157	55	2.165	594	67	1039	116	23.5	51.7
F-8.1019.0	280	11.000	364	14.331	330	12.992	300	11.811	10	0.394	65	2.559	594	67	1039	116	25.0	55.0
F-8.419.5	305	12.000	385	15.157	355	13.976	325	12.795	4	0.157	60	2.362	640	71	1121	125	16.0	35.2
F-8.1019.5	305	12.000	392	15.433	355	13.976	325	12.795	10	0.394	70	2.756	640	71	1121	125	24.8	54.6
F-8.420.0	308	12.125	400	15.748	366	14.409	330	12.992	4	0.157	60	2.362	787	88	1377	154	20.0	44.0
F-8.1020.0	308	12.125	406	15.984	366	14.409	330	12.992	10	0.394	70	2.756	787	88	1377	154	35.0	77.0
F-8.1021.0	336	13.250	448	17.638	400	15.748	360	14.173	10	0.157	70	2.756	955	107	1671	187	39.0	85.8
F-8.1022.0	366	13.250	460	18.110	422	16.614	390	15.354	10	0.394	70	2.756	816	91	1428	160	37.0	81.4
F-8.1023.0	396	15.625	486	19.134	450	17.717	420	16.535	10	0.157	70	2.756	820	92	1435	161	32.5	71.5

Special features or requirements can be accommodated. Kindly contact your local agent or call our office directly.

