



F-Type Nuts

STANDARD SERIES F-9.4 & F-9.10

with AXIAL F-NIPPLE & RELEASE SCREW

Actuated by manual or motorized grease pump. Self-aligning annular thrust ring with 4 or 10 mm maximum axial travel.

Model	Max Arbor Thread Size		Cannot Exceed Minimum Tool Ø		Verify diameters D & E contact an uninterrupted surface				Select Stroke as Required		Ensure Adequate Force Has Been Selected				Weight			
	Max Thread Ø		Nut Diameter		Thrust Ring Size				Thrust Ring Stroke		Nut Width		Clamping Force					
	A		B		D - OD		E - ID		S		C		400 BAR		700 BAR			
	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	kN	Tons	kN	Tons	KG	Pounds
F-9.405	36	1.750	82	3.228	66	2.598	46	1.811	4	0.157	50	1.969	70	8	123	13	3.0	6.6
F-9.1005	36	1.750	85	3.346	66	2.598	46	1.811	10	0.394	60	2.362	70	8	123	13	3.0	6.6
F-9.407	52	2.000	98	3.858	82	3.228	62	2.441	4	0.157	50	1.969	90	10	158	18	3.0	6.6
F-9.1007	52	2.000	102	4.016	82	3.228	62	2.441	10	0.394	60	2.362	90	10	158	18	3.0	6.6
F-9.408	68	2.625	116	4.567	100	3.937	80	3.150	4	0.157	50	1.969	113	13	198	22	3.0	6.6
F-9.1008	68	2.625	120	4.724	100	3.937	80	3.150	10	0.394	60	2.362	113	13	198	22	3.4	7.5
F-9.409	82	3.250	131	5.157	115	4.528	95	3.740	4	0.157	50	1.969	131	14	230	26	3.4	7.5
F-9.1009	82	3.250	135	5.315	115	4.528	95	3.740	10	0.394	60	2.362	131	14	230	26	4.0	8.8
F-9.410	100	3.875	148	5.827	130	5.118	112	4.409	4	0.157	50	1.969	137	15	239	27	4.5	9.9
F-9.1010	100	3.875	152	5.984	130	5.118	112	4.409	10	0.394	60	2.362	137	15	239	27	5.8	12.8
F-9.411	125	4.875	180	7.087	160	6.299	138	5.433	4	0.157	50	1.969	205	23	360	40	5.1	11.2
F-9.1011	125	4.875	185	7.283	160	6.299	138	5.433	10	0.394	60	2.362	205	23	360	40	6.8	15.0
F-9.412	142	5.625	195	7.677	175	6.890	155	6.102	4	0.157	50	1.969	207	23	363	41	5.5	12.1
F-9.1012	142	5.625	200	7.874	175	6.890	155	6.102	10	0.394	60	2.362	207	23	363	41	7.3	16.1
F-9.4125	156	6.125	210	8.268	190	7.480	170	6.693	4	0.157	50	1.969	226	25	396	45	6.0	13.2
F-9.10125	156	6.125	215	8.465	190	7.480	170	6.693	10	0.394	60	2.362	226	25	396	45	8.5	18.7
F-9.413	165	6.500	220	8.661	200	7.874	180	7.087	4	0.157	50	1.969	238	27	417	47	8.0	17.6
F-9.1013	165	6.500	228	8.976	200	7.874	180	7.087	10	0.394	60	2.362	238	27	417	47	11.0	24.2
F-9.414	186	7.375	242	9.528	222	8.740	202	7.953	4	0.157	50	1.969	266	30	466	52	8.5	18.7
F-9.1014	186	7.375	250	9.843	222	8.740	202	7.953	10	0.394	60	2.362	266	30	466	52	12.0	26.4
F-9.415	198	7.750	262	10.315	240	9.449	215	8.465	4	0.157	50	1.969	357	40	625	70	9.0	19.8
F-9.1015	198	7.750	268	10.551	240	9.449	215	8.465	10	0.394	60	2.362	357	40	625	70	13.5	29.7

Special features or requirements can be accommodated. Kindly contact your local agent or call our office directly.

